



Project: Date:

Prepared By:

Comments:



FEATURES

- White gimbal trim, pivots and turns
- IC rated for contact with insulation
- Dimmable to 10% with approved LED dimmers
- Wet-location rated
- Title 24 Compliant (CRI >90)
- ENERGY STAR®

APPLICATIONS

- Conference Room
- Medical Office
- Office Lobby
- Residential
- Retail

OPTICS

- Frosted white lens
- Regressed reflector

CERTIFICATIONS

... Visit our website for more information.

TRIM ORDERING OPTIONS

| Model Number | Kelvin (CCT) | Watts | Lumens | CRI | Trim Color |
|--------------|--------------|-------|--------|-----|----------------------------|
| EVL4742AWH40 | 4000K | 10 | 649 | 90 | White Retrofit Trim-Gimbal |
| EVL4742BWH40 | 4000K | 8.8 | 649 | 90 | White Retrofit Trim-Gimbal |

SPECIFICATIONS

| | | | | | | |
|----------------|------------|--------------------|--------|---------------|-------------|------|
| Warranty: | 5 Years | Max. Ambient Temp: | 45° C | R9-Value: | Beam Angle: | 103° |
| Expected Life: | 50,000 hrs | Min. Ambient Temp: | -18° C | Power Factor: | THD: | <20% |





Project: Date:

Prepared By:

Comments

DIMMING COMPATIBILITY

DIMENSIONS

Photometrics